

Y.B.

L^AT_EX Class yb-book*

Yegor Bugayenko
yegor256@gmail.com

2026-05-31, 0.11.0

1 Introduction

The class yb-book was devised to assist the author in producing [his books](#) and in publishing them [on Amazon](#). Others are welcome to employ it for their own books. The procedure is straightforward:

```
\documentclass{yb-book}
\renewcommand*\thetitle{New Book About OOP}
\renewcommand*\theauthor{Jeff Lebowski}
\renewcommand*\thevolume{1}
\renewcommand*\theversion{1.0}
\begin{document}
\ybPrintTitlePage
\chapter{First One}
\section{About Something Interesting}
Hello, world!
\end{document}
```

Suggestions for additional options and commands are welcome; nevertheless, the style of the author's books is intentionally as plain as possible, eschewing formatting to the greatest extent practicable. The reasoning is set out [here](#).

2 Options

Several class options are available:

compact This package option is to be used when the text is required in a more compact form, occupying less vertical space. It proves convenient for works of fiction. The author employs it to render the [Code Ahead](#) book.

sparse Under this package option, every section commences on a new page.

*The sources are on GitHub at [yegor256/yb-book](#)

- manuscript** Whenever the format is not intended for Amazon printing but for some other purpose (the page size being A4), this option proves convenient. The author likewise employs it whenever the book is to be rendered for printing on paper for review purposes.
- authordraft** This option is appropriate when the document is a draft for reviewers (the page size being A4) and a watermark together with a compact form of the content is desired. The option is used in conjunction with the `\thereviewer{}` command, which may be redefined to embed the name of the reviewer within the watermark. This serves as a deterrent to theft of the book:

```
\documentclass[authordraft]{yb-book}
\renewcommand*\thereviewer{Walter Sobchak}
\begin{document}
Hello, world!
\end{document}
```

3 Meta Commands

A number of commands may be redefined within the preamble:

```
\documentclass{yb-book}
\newcommand*\thetitle{My New Book About OOP}
\newcommand*\theauthor{Yegor Bugayenko}
\newcommand*\thevolume{1}
\newcommand*\thedata{24 Feb 2022}
\newcommand*\theversion{1.4}
\newcommand*\thereviewer{Jeff Lebowski}
\begin{document}
... the content goes here ...
\end{document}
```

4 Printers

A number of printers are provided—commands that render substantial blocks of text in the expected format:

- `\ybPrintTitlePage` Prints the first page of a book. At minimum, `\thetitle` and `\theauthor` must be defined:

```
\documentclass{yb-book}
\renewcommand*\thetitle{My New Book}
\renewcommand*\theauthor{Yegor Bugayenko}
\begin{document}
\ybPrintTitlePage
.. the rest of the book goes here
\end{document}
```

- `\ybPrintTOC` Prints the table of contents.

- `\ybQuote` Prints a side quote:

```
\documentclass{yb-book}
```

```

\begin{document}
Hello, world!
\ybQuote{Never tell the truth to people who
are not worthy of it}{Mark Twain}{}
\end{document}

```

A warning is emitted to the log whenever the quotation falls very close to the top or the bottom of a page, since the underlying `wrapfig` environment behaves poorly in such positions.

`\ybPrintBibliography` Prints the list of bib references.

`\ybPrintIndex` Prints index with an optional name of the section (instead of “Index”):

```

\documentclass{yb-book}
\begin{document}
Hello, world!
\ybPrintIndex[Recommended Books]
\end{document}

```

5 Implementation

First, we parse package options:

```

1 \RequirePackage{pgfopts}
2 \pgfkeys{
3   /yb/.cd,
4   apa/.store in=\yb@apa,
5   authordraft/.store in=\yb@authordraft,
6   compact/.store in=\yb@compact,
7   manuscript/.store in=\yb@manuscript,
8   colored/.store in=\yb@colored,
9   sparse/.store in=\yb@sparse,
10 }
11 \ProcessPgfPackageOptions{/yb}

```

Then, depending on the options like `authordraft` and `manuscript`, we preset options of the class `book` and then load it:

```

12 \makeatletter
13 \ifdefined\yb@authordraft
14   \PassOptionsToClass{11pt}{book}
15   \PassOptionsToClass{oneside}{book}
16 \else
17   \ifdefined\yb@manuscript
18     \PassOptionsToClass{12pt}{book}
19     \PassOptionsToClass{oneside}{book}
20   \else
21     \PassOptionsToClass{11pt}{book}
22     \PassOptionsToClass{twoside}{book}
23   \fi
24 \fi
25 \makeatother
26 \LoadClass{book}

```

Then, we load `href-ul` to underline links correctly:

```

27 \RequirePackage{href-ul}

```

Then, we load [cleveref](#) for the `\cref` command:

```
28 \PassOptionsToPackage{capitalize}{cleveref}
29 \RequirePackage{amsmath}
30 \RequirePackage{cleveref}
31 \crefformat{section}{\S#2#1#3}
```

The class does not change the main font; the default Computer Modern Roman is used. Document authors are free to select a different font in their own preamble.

`geometry` Then, using `geometry`, we set up page layout:

```
32 \RequirePackage{geometry}
33 \geometry{
34   paperwidth=6in, paperheight=9in,
35   bindingoffset=0.25in,
36   left=0.75in, right=0.75in, top=0.75in, bottom=1.25in}
37 \makeatletter
38 \ifdefined\yb@authordraft
39   \geometry{a4paper, margin=1in, left=1.5in}
40 \else
41   \ifdefined\yb@manuscript
42     \geometry{a4paper, margin=1.2in}
43   \fi
44 \fi
45 \makeatother
```

Then, we load [anyfontsize](#) to enable all sizes of fonts:

```
46 \RequirePackage{anyfontsize}
```

Then, we load [tikz](#) for graphics:

```
47 \RequirePackage{tikz}
48 \usetikzlibrary{positioning}
49 \usetikzlibrary{shapes}
50 \usetikzlibrary{fit}
```

Then, we load [chngcntr](#) for something else:

```
51 \RequirePackage{chngcntr}
52 \counterwithout{footnote}{chapter}
```

Then, we load [lastpage](#) to enable rendering of the last page number:

```
53 \RequirePackage{lastpage}
```

Then, we load [paralist](#) for inline enumeration:

```
54 \RequirePackage{paralist}
```

Then, we load [xcolor](#) for colors:

```
55 \RequirePackage{xcolor}
```

Then, we load [graphicx](#) to enable graphic files inclusion:

```
56 \RequirePackage{graphicx}
```

Then, we load [enumitem](#) for inline enumeration:

```
57 \PassOptionsToPackage{inline}{enumitem}
58 \RequirePackage{enumitem}
59 \setlist{nosep}
```

Then, we load [float](#) for floating figures:

```
60 \RequirePackage{float}
```

Then, we load [xfp](#) and [xifthen](#) for if-then-else:

```
61 \RequirePackage{xfp}
62 \RequirePackage{xifthen}
```

Then, we load [csquotes](#) for better rendering:

```
63 \PassOptionsToPackage{autostyle=try}{csquotes}
64 \RequirePackage{csquotes}
```

`\pagestyle` Then, we set the layout of a page to `plain`:

```
65 \pagestyle{plain}
```

`setspace` Then, using `setspace` package we set the spacing between lines in the text, depending on the package options:

```
66 \RequirePackage{setspace}
67 \setstretch{1.2}
68 \makeatletter
69 \ifdefined\yb@compact\setstretch{1.0}\fi
70 \ifdefined\yb@manuscript\setstretch{1.1}\fi
71 \ifdefined\yb@authordraft\setstretch{1.4}\fi
72 \makeatother
```

`biblatex` Then, we configure `biblatex` for citation management:

```
73 \PassOptionsToPackage{indexing=cite,
74   natbib=true,maxnames=2,minnames=1,doi=true,
75   url=false,isbn=false}{biblatex}
76 \makeatletter
77 \ifdefined\yb@apa
78   \PassOptionsToPackage{style=authoryear}{biblatex}
79 \else
80   \PassOptionsToPackage{style=numeric}{biblatex}
81 \fi
82 \makeatother
83 \RequirePackage{doi}
84 \RequirePackage{biblatex}
85 \DeclareCiteCommand{\citetitle}
86   {\boolfalse{citetracker}%
87    \boolfalse{pagetracker}%
88    \usebibmacro{prenote}}
89   {\ifciteindex
90     {\indexnames{labelname}}
91     {}%
92    \printfield[citetitle]{labeltitle}}
93   {\multicitedelim}
94   {\usebibmacro{postnote}}
95 \DeclareCiteCommand*{\citetitle}
96   {\boolfalse{citetracker}%
97    \boolfalse{pagetracker}%
98    \usebibmacro{prenote}}
99   {\ifciteindex
100     {\indexnames{labelname}}
101     {}%
102    \printfield[citetitle]{title}}
103   {\multicitedelim}
104   {\usebibmacro{postnote}}
```

`condensed` Then, we define `condensed` environment for snippets:

```
105 \newenvironment{condensed}
106   {\begingroup%
107     \lstset{columns=fixed, basewidth=0.45em}}
108   {\endgroup}
```

`microtype` Then, we include `microtype` for better rendering:

```
109 \makeatletter
110 \ifdefined\yb@authordraft
111   \PassOptionsToPackage{nopatch=footnote}{microtype}
112 \else
113   \PassOptionsToPackage{nopatch=footnote, protrusion=true}{microtype}
114 \fi
115 \makeatother
116 \RequirePackage{microtype}
```

`\section` Then, we redefine the `\section` command:

```
117 \makeatletter
118 \let\yb@oldsection\section
119 \def\yb@secstart{\ifdefined\yb@sparse\newpage\fi}
120 \ifdefined\yb@authordraft
121   \PassOptionsToPackage{medium}{titlesec}
122   \RequirePackage{titlesec}
123 \else
124   \PassOptionsToPackage{raggedright}{titlesec}
125   \RequirePackage{titlesec}
126   \titlespacing{\section}{0em}{2em}{1em}
127   \renewcommand\section{\yb@secstart\yb@oldsection}
128 \fi
129 \ifdefined\yb@compact
130   \renewcommand\section{\yb@secstart\vspace{2em}\yb@oldsection}
131 \fi
132 \makeatother
```

Then, we do small tweaking:

```
133 \makeatletter
134 \renewcommand\@makefnmark[1]{%
135   \raggedright%
136   \parindent=1em%
137   \noindent\hb@xt@1.8em{\hss\@makefnmark}#1}
138 \makeatother
```

Then, if it's an `authordraft`, we put a watermark comment:

```
139 \makeatletter
140 \ifdefined\yb@authordraft
141   \PassOptionsToPackage{absolute}{textpos}
142   \RequirePackage{textpos}
143   \TPGrid{16}{16}
144   \RequirePackage{fancyhdr}
145   \pagestyle{fancy}
146   \renewcommand\headrulewidth{0em}
147   \renewcommand\footrulewidth{0em}
148   \setlength{\headheight}{3em}
149   \fancyhf{}
```

```

150 \fancyhead[L,C,L0,C0]{%
151 \fancyhead[R,R0]{%
152 \begin{textblock}{16}[0.5,0.5](8,8)%
153 \tikz \node[minimum width=16\TPHorizModule] {%
154 \fontsize{64}{64}\selectfont\bfseries%
155 \rotatebox{45}{%
156 \tikz \node
157 [fill=gray!6, font=\ttfamily\color{white}]
158 {it is a draft};%
159 }%
160 };%
161 \end{textblock}%
162 \begin{textblock}{4}(11.5,1)%
163 \tikz \node [color=gray, rotate=270,
164 font=\ttfamily\scriptsize, text width=24em] at (0,0) {%
165 Copyright \textcopyright{} \the\year{} by \theauthor{}.
166 All rights reserved. No part of the contents of
167 this book may be reproduced or transmitted in any
168 form or by any means without the written permission
169 of the publisher. This particular manuscript is
170 printed for \textbf{\thereviewer{}} and may be used only
171 for one-time review. The manuscript has to be destroyed
172 after the review.%
173 };
174 \end{textblock}
175 }
176 \fancyfoot[C,C0,C]{\small\ttfamily%
177 page \thepage{} of \pageref{LastPage}}
178 \fi
179 \makeatother

```

`\maketitle` Then, we redefine the `\maketitle` command:

```

180 \renewcommand\maketitle{
181 {\LARGE\textbf{\thetitle}}
182 \\\[1em]
183 by \theauthor{}
184 \\\[4em]
185 \ifx\thevolume\empty\else%
186 Volume \thevolume{}\\\
187 \fi
188 \ifx\thedata\empty\else%
189 Rendered on \thedata{}\\\
190 \fi
191 \ifx\theversion\empty\else%
192 Ver. \theversion{}
193 \fi
194 }

```

`\incolor` Then, we define the `\incolor` command:

```

195 \makeatletter
196 \newcommand\incolor[2]{%
197 \ifdefined\yb@colored\textcolor{#1}{#2}\else#2\fi}
198 \makeatother

```

\ix Then, we define the \ix command:

```
199 \newcommand\ix[2] []{%
200   \incolor{brown}{#2}%
201   \def\ixparam{#1}%
202   \ifx\ixparam\empty%
203     \index{#2}%
204   \else%
205     \index{#1}%
206   \fi}
```

\emph Then, we redefine the \emph command:

```
207 \renewcommand\emph[1]{\incolor{orange}{\textit{#1}}}
```

\ybPrintTitlePage Then, we define the \ybPrintTitlePage command:

```
208 \makeatletter
209 \newcommand\ybPrintTitlePage{
210   \ifdefined\yb@authordraft\else
211     \begin{titlepage}
212       \ttfamily
213       \vspace*{\fill}
214       \noindent
215       {\Huge\thetitle}
216       \\[1em]
217       by \theauthor{}
218       \\[4em]
219       \ifx\thevolume\empty\else%
220         Volume \thevolume{}\\\
221       \fi
222       \ifx\thedata\empty\else%
223         \thedata{}\\\
224       \fi
225       \ifx\theversion\empty\else%
226         \theversion{}
227       \fi
228       \vspace*{\fill}
229     \end{titlepage}
230   \fi
231 }
232 \makeatother
```

\ybEpigraph Then, we define the \ybEpigraph command to print the epigraph:

```
233 \newcommand\ybEpigraph[3]{
234   \cleardoublepage
235   \vspace*{\fill}
236   \begin{quote}
237     \begin{raggedleft}
238       ‘‘#1’’ \\[1em]
239       {---} #2 \\
240       \citetitle{#3}\\
241       \citeyear{#3}\par
242     \end{raggedleft}
243   \end{quote}
244   \vspace*{\fill}}
```


`\ybPrintTOC` Then, we define the `\ybPrintTOC` command to print the table of contents:

```

245 \makeatletter
246 \newcommand\ybPrintTOC{%
247   \ifdefined\yb@authordraft\else%
248     \ifdefined\yb@compact\else\cleardoublepage\fi%
249     {\setstretch{0.7}\tableofcontents}%
250   \fi%
251 }
252 \makeatother

```

`\ybPrintIndex` Then, we configure the `imakeidx` package and define the `\ybPrintIndex` command:

```

253 \RequirePackage{imakeidx}
254 \renewbibmacro*{citeindex}{\indexnames{labelname}{}}
255 \makeindex
256 \indexsetup{othercode={\hyphenpenalty=10000}}
257 \makeatletter
258 \newcommand\ybPrintIndex[1][Index]{%
259   \ifdefined\yb@authordraft\else%
260     \ifdefined\yb@compact\else\cleardoublepage\fi%
261   {%
262     \setstretch{1.0}%
263     \small%
264     \addcontentsline{toc}{chapter}{#1}%
265     \printindex%
266   }%
267   \fi%
268 }
269 \makeatother

```

`\ybQuote` Then, with the help of `wrapfig` and `mdframed`, we define the `\ybQuote` command:

```

270 \RequirePackage{wrapfig}
271 \RequirePackage{mdframed}
272 \RequirePackage{changepage}
273 \strictpagecheck
274 \mdfdefinestyle{quoteodd}{backgroundcolor=black!0,
275   leftmargin=1em,rightmargin=0em,
276   innerleftmargin=1em,innerrightmargin=0em,
277   innertopmargin=0em,innerbottommargin=0em,
278   skipabove=0em,skipbelow=0em,
279   linewidth=.2em,
280   topline=false,bottomline=false,rightline=false}
281 \mdfdefinestyle{quoteeven}{backgroundcolor=black!0,
282   rightmargin=1em,leftmargin=0em,
283   innerrightmargin=1em,innerleftmargin=0em,
284   innertopmargin=0em,innerbottommargin=0em,
285   skipabove=0em,skipbelow=0em,
286   linewidth=.2em,
287   topline=false,bottomline=false,leftline=false}
288 \makeatletter
289 \newcommand\ybQuote[3]{%
290   \ifthenelse{\isempty{#3}}{}{
291     \ifx\hfuzz#2\hfuzz%
292       \index{#3}%
293     \else%

```

```

294     \index{#3, #2}%
295     \fi%
296 }%
297 \ifdim\pagetotal<4\baselineskip\relax%
298   \ClassWarning{yb-book}{ybQuote stays at the top of a page: \detokenize{#1}}%
299 \fi%
300 \ifdim\dimexpr\pagegoal-\pagetotal\relax<8\baselineskip\relax%
301   \ClassWarning{yb-book}{ybQuote stays at the bottom of a page: \detokenize{#1}}%
302 \fi%
303 \def\yb@body{%
304   \raggedright%
305   \ifx\hfuzz#3\hfuzz%
306     #1%
307   \else%
308     ‘‘#1’’\\raggedleft---#2 #3%
309   \fi%
310 }
311 \ifdefined\yb@authordraft%
312   \begin{wrapfigure}{r}{0.4\textwidth}%
313     \begin{mdframed}[style=quoteodd]%
314       \yb@body%
315     \end{mdframed}%
316   \end{wrapfigure}%
317 \else%
318   \begin{wrapfigure}{o}{2em}{0.4\textwidth}%
319     \sffamily\checkoddpage%
320     \ifoddpage%
321       \begin{mdframed}[style=quoteodd]\yb@body\end{mdframed}%
322     \else%
323       \begin{mdframed}[style=quoteeven]\yb@body\end{mdframed}%
324     \fi%
325     \vspace{-1em}
326   \end{wrapfigure}%
327 \fi%
328 }
329 \makeatother

```

\ybQuote Then, we define the \ybTweet command:

```

330 \makeatletter
331 \newcommand\ybTweet[1]{%
332   \ifdefined\yb@authordraft\else%
333     \ybQuote{#1}{-}{-}%
334   \fi%
335 }
336 \makeatother

```

Then, we use and configure footmisc as suggested [here](#):

```

337 \RequirePackage{perpage}
338 \PassOptionsToPackage{bottom,perpage,multiple}{footmisc}
339 \RequirePackage{footmisc}
340 \makeatletter
341 \let\yb@oldfootnote\footnote
342 \newcommand\yb@nexttoken\relax
343 \newcommand\yb@isfootnote{%

```

```

344 \ifx\footnote\yb@nexttoken\textsuperscript{,}\fi}
345 \renewcommand\footnote[1]{%
346 \yb@oldfootnote{#1}\futurelet\yb@nexttoken\yb@isfootnote}
347 \makeatother

```

`\ybPrintBibliography` Then, we define `\ybPrintBibliography`, to print a list of references:

```

348 \makeatletter
349 \newcommand\ybPrintBibliography[1][Bibliography]{%
350 \AtNextBibliography{\small}%
351 \raggedright%
352 \ifdefined\yb@manuscript%
353 \setlength\bibitemsep{0em}%
354 \newpage%
355 \begin{multicols}{2}%
356 {\setstretch{1.0}\printbibliography}%
357 \end{multicols}%
358 \else%
359 \setlength\bibitemsep{.2em}%
360 \@openrightfalse%
361 \printbibliography[heading=bibintoc,title={#1}]%
362 \ifdefined\yb@compact\@openrighttrue\fi%
363 \fi%
364 }
365 \makeatother

```

`\highlight` Then, we define the `\highlight` command:

```

366 \makeatletter
367 \newcommand\highlight[1]{%
368 \tikz[baseline=(text.base)] {
369 \node[inner sep=0em, outer sep=0em] (text) {%
370 {\ifdefined\yb@colored\color{orange}\fi#1}};
371 \begin{scope}
372 \path[use as bounding box] (text.east) rectangle (text.west);
373 \draw[decorate,
374 decoration={random steps, amplitude=0.05em, segment length=0.3em},
375 line join=round,
376 line cap=round,
377 line width=.08em,
378 draw=gray!80] ($(text.west) + (-0.2em, -.46em)$) rectangle ($(text.east) + (+0.2em, -
379 \end{scope}
380 }%
381 }
382 \makeatother

```

Then, a few layout configurations at the beginning of the document:

```

383 \makeatletter
384 \AtBeginDocument{%
385 \raggedbottom%
386 \ifdefined\yb@authordraft%
387 \raggedright%
388 \fi%
389 \setlength\topskip{0em}%
390 \setlength\parindent{0em}%
391 \setlength\fbboxsep{0em}%

```

```

392 \setlength\parskip{.5em}%
393 \exhyphenpenalty=10000% to avoid line breaks before and after an em dash
394 \widowpenalty=10000% to have fewer widows
395 \clubpenalty=10000% to have fewer orphans
396 \interfootnotelinepenalty=10000% to format footnotes better
397 \hfuzz=3pt %
398 \tolerance=1000 %
399 \emergencystretch=1em %
400 \hbadness=2000 %
401 }
402 \makeatother

```

Finally, a few meta commands with default values:

```

403 \newcommand*\thetitle{\textbackslash{}thetitle}
404 \let\thevolume\empty
405 \let\thedata\empty
406 \newcommand*\theversion{\textbackslash{}theversion}
407 \newcommand*\theauthor{\textbackslash{}theauthor}
408 \newcommand*\thereviewer{\textbackslash{}thereviewer}
409
410 \endinput

```

Change History

v0.1.0		added, to enable APA citation style.	3
General: Initial version	3		
v0.11.0			
\ybQuote: The \ybTweet command added.	10	v0.6.2	
v0.2.0		\ybPrintBibliography: The \ybPrintBibliography command has an optional argument, which is the title of the chapter.	11
General: Started using l3build . . .	3		
v0.3.0			
General: The pgfopts package is now used to parse package options.	3	v0.6.6	
v0.4.0		General: Penalties for widows and clubs specified.	11
authordraft: The package option draft renamed to authordraft	2	v0.7.0	
v0.5.0		General: Added cleveref package for the \cref command.	4
General: The sparse package option added, to place every section on a new page.	3	The colored package option added, to enable colors.	3
v0.5.1		\highlight: The \highlight command was added.	11
General: Added the usage of inputenc in order to ensure UTF-8 encoding for the sources.	4	v0.8.1	
v0.6.0		General: Removed the CMU Concrete font setup; the class no longer changes the main font and works under any engine. . .	4
General: The apa package option			

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	<code>\endinput</code> 410	<code>\interfootnotelinepenalty</code> 396
<code>\@makefnmark</code> 137	<code>\exhyphenpenalty</code> .. 393	<code>\ix</code> 199
<code>\@makefntext</code> 134	F	<code>\ixparam</code> 201, 202
<code>\@openrightfalse</code> .. 360	<code>\fancyfoot</code> 176	L
<code>\@openrighttrue</code> ... 362	<code>\fancyhead</code> 150, 151	<code>\LARGE</code> 181
<code>\</code> 182, 184, 186, 189, 216, 218, 220, 223, 238, 239, 240, 308	<code>\fancyhf</code> 149	<code>\LoadClass</code> 26
A	<code>\fboxsep</code> 391	<code>\lstset</code> 107
<code>\addcontentsline</code> .. 264	<code>\fill</code> . 213, 228, 235, 244	M
<code>Amazon</code> 1	<code>\fontsize</code> 154	<code>\makeatletter</code> .. 12, 37, 68, 76, 109, 117, 133, 139, 195, 208, 245, 257, 288, 330, 340, 348, 366, 383
<code>\AtBeginDocument</code> .. 384	<code>\footnote</code> . 341, 344, 345	<code>\makeatother</code> ... 25, 45, 72, 82, 115, 132, 138, 179, 198, 232, 252, 269, 329, 336, 347, 365, 382, 402
<code>\AtNextBibliography</code> 350	<code>\footrulewidth</code> 147	<code>\makeindex</code> 255
<code>\authordraft</code> 1	<code>\futurelet</code> 346	<code>\maketitle</code> 180
B	G	<code>\manuscript</code> 1
<code>\baselineskip</code> . 297, 300	<code>\geometry</code> <u>32</u> , 33, 39, 42	<code>\mdfdefinestyle</code> 274, 281
<code>\bfseries</code> 154	H	<code>\microtype</code> 109
<code>\bibitemsep</code> ... 353, 359	<code>\hb@xt@</code> 137	<code>\multicitedelim</code> 93, 103
<code>\biblatex</code> 73	<code>\hbadness</code> 400	N
<code>\boolfalse</code> 86, 87, 96, 97	<code>\headheight</code> 148	<code>\newpage</code> 119, 354
C	<code>\headrulewidth</code> 146	<code>\node</code> . 153, 156, 163, 369
<code>\checkoddpage</code> 319	<code>\hfuzz</code> 291, 305, 397	<code>\noindent</code> 137, 214
<code>\citetitle</code> .. 85, 95, 240	<code>\highlight</code> 366	P
<code>\citeyear</code> 241	<code>\hss</code> 137	<code>\pagegoal</code> 300
<code>\ClassWarning</code> . 298, 301	<code>\Huge</code> 215	<code>\pageref</code> 177
<code>\cleardoublepage</code> 234, 248, 260	<code>\hyphenpenalty</code> 256	<code>\pagestyle</code> 65, 145
<code>\clubpenalty</code> 395	I	<code>\pagetotal</code> 297, 300
<code>\color</code> 157, 370	<code>\ifcindex</code> 89, 99	<code>\par</code> 241
<code>\compact</code> 1	<code>\ifdefined</code> 13, 17, 38, 41, 69, 70, 71, 77, 110, 119, 120, 129, 140, 197, 210, 247, 248, 259, 260, 311, 332, 352, 362, 370, 386	<code>\parindent</code> 136, 390
<code>\condensed</code> 105	<code>\ifdim</code> 297, 300	<code>\parskip</code> 392
<code>\counterwithout</code> ... 52	<code>\ifoddpage</code> 320	<code>\PassOptionsToClass</code> 14, 15, 18, 19, 21, 22
<code>\crefformat</code> 31	<code>\ifthenelse</code> 290	<code>\PassOptionsToPackage</code> .. 28, 57, 63, 73,
D	<code>\ifx</code> ... 185, 188, 191, 202, 219, 222, 225, 291, 305, 344	
<code>\DeclareCiteCommand</code> 85, 95	<code>\incolor</code> .. 195, 200, 207	
<code>\detokenize</code> ... 298, 301	<code>\index</code> 203, 205, 292, 294	
<code>\dimexpr</code> 300	<code>\indexnames</code> 90, 100, 254	
<code>\draw</code> 373	<code>\indexsetup</code> 256	
E		
<code>\emergencystretch</code> .. 399		
<code>\emph</code> 207		

78, 80, 111, 113, 121, 124, 141, 338	\setstretch .. 67, 69, 70, 71, 249, 262, 356	\usetikzlibrary 48, 49, 50
\path 372	\sffamily 319	V
\pgfkeys 2	\small 176, 263, 350	\vspace ... 130, 213, 228, 235, 244, 325
\printbibliography 356, 361	\sparse 1	
\printfield 92, 102	\strictpagecheck .. 273	
\printindex 265	T	W
\ProcessPgfpPackageOptions 11	\tableofcontents .. 249	\widowpenalty 394
R	\textbackslash 403, 406, 407, 408	Y
\raggedbottom 385	\textbf 170, 181	\yb@apa 4, 77
\raggedleft 308	\textcolor 197	\yb@authordraft 5, 13, 38, 71, 110, 120, 140, 210, 247, 259, 311, 332, 386
\raggedright 135, 304, 351, 387	\textcopyright 165	\yb@body 303, 314, 321, 323
\relax 297, 300, 342	\textit 207	\yb@colored . 8, 197, 370
\renewbibmacro 254	\textsuperscript .. 344	\yb@compact ... 6, 69, 129, 248, 260, 362
\renewcommand .. 127, 130, 134, 146, 147, 180, 207, 345	\textwidth 312, 318	\yb@isfootnote 343, 346
\RequirePackage 1, 27, 29, 30, 32, 46, 47, 51, 53, 54, 55, 56, 58, 60, 61, 62, 64, 66, 83, 84, 116, 122, 125, 142, 144, 253, 270, 271, 272, 337, 339	\the 165	\yb@manuscript 7, 17, 41, 70, 352
\rotatebox 155	\theauthor 165, 183, 217, 407	\yb@nexttoken 342, 344, 346
S	\thedata 188, 189, 222, 223, 405	\yb@oldfootnote 341, 346
\S 31	\thepage 177	\yb@oldsection 118, 127, 130
\scriptsize 164	\thereviewer .. 170, 408	\yb@secstart 119, 127, 130
\section 117	\thetitle . 181, 215, 403	\yb@sparse 9, 119
\selectfont 154	\theversion 191, 192, 225, 226, 406	\yb@Epigraph 233
\setlength 148, 353, 359, 389, 390, 391, 392	\thevolume 185, 186, 219, 220, 404	\ybPrintBibliography 1, 348
\setlist 59	\tikz . 153, 156, 163, 368	\ybPrintIndex ... 1, 253
\setspace 66	\titlespacing 126	\ybPrintTitlePage 1, 208
	\tolerance 398	\ybPrintTOC 1, 245
	\topskip 389	\ybQuote ... 1, 270, 330
	\TPGrid 143	\ybTweet 331
	\TPHorizModule 153	\year 165
	\ttfamily 157, 164, 176, 212	
	U	
	\usebibmacro 88, 94, 98, 104	